



Industrial MF5A Temperature NTC Thermistor Stable Epoxy Enameled Wire

Our Product Introduction

for more products please visit us on lk-thermistor.com

Basic Information

- Place of Origin: Dongguan China
- Brand Name: linkun
- Certification: CE / ROHS / UL / TUV / SGS
- Model Number: Temperature NTC Thermistor
- Minimum Order Quantity: Negotiation
- Price: Negotiation
- Packaging Details: Export Package / Negotiation
- Delivery Time: Negotiation
- Payment Terms: T/T, L/C, Western Union
- Supply Ability: 24 million per year




Product Specification

- Features: Fast Response Time
- Application: Electronic Product / Industrial Products
- Operating Temperature: -55C~+125C.
- Technology: Ceramic Composition
- Wide Choice Of B Values: 2600~4900K
- Temperature Range: $\pm 5\%$, $\pm 10\%$, $\pm 20\%$
- Highlight: Industrial Temperature NTC Thermistor, MF5A Temperature NTC Thermistor, Stable Epoxy Thermistor



More Images



Product Description

Small Volume MF5A Temperature NTC Thermistor Epoxy Enameled Wire Stability And Reliability

The temperature sensor has the following characteristics:

NTC thermistors are used in a wide range of applications. They are used to measure temperature, control temperature and temperature compensation. They can also be used to detect the absence or presence of liquids, as a current limiting device in power circuits, temperature monitoring in automotive applications, and more. NTC sensors can be divided into three groups depending on the electrical characteristics used in the application.

1. Resistance - Temperature Characteristics


Applications based on resistance-time characteristics include temperature measurement, control and compensation. These also include the case of using NTC thermistors, making the temperature of the NTC temperature sensor related to some other physical phenomenon. This group of applications requires the thermistor to operate under zero power conditions, meaning that the current through it is kept as low as possible to avoid heating the probe.

2. Current time characteristics

Applications based on current-time characteristics include: time delay, inrush current limiting, inrush suppression, and more. These characteristics are related to the heat capacity and dissipation constant of the NTC thermistor used. Circuits often rely on the heating of the NTC thermistor due to the passage of current. At some point, it will trigger some kind of change in the circuit, depending on the application it's being used in.

3. Voltage-Current Characteristics


Applications based on the thermistor's voltage-current characteristics often involve changes in environmental conditions or circuit changes, which result in changes in the operating point on a given curve in the circuit. Depending on the application, it can be used for current limiting, temperature compensation or temperature measurement.



Product parameters

P/N	R@25°C	Tolerance(%)	Beta Value	Tolerance(%)
MF11-050	5		2400	
MF11-100	10		2800	
MF11-150	15		2800	
MF11-200	20		2800	
MF11-220	22		2800	
MF11-270	27		3000	
MF11-330	33		3000	
MF11-390	39		3000	
MF11-470	47		3100	
MF11-500	50		3100	
MF11-680	68		3100	
MF11-820	82		3100	
MF11-101	100		3200	
MF11-121	120		3200	
MF11-151	150		3200	
MF11-201	200		3200	
MF11-221	220		3500	
MF11-271	270		3500	
MF11-331	330		3500	
MF11-391	390		3500	
MF11-471	470		3500	
MF11-501	500		3500	
MF11-561	560		3500	
MF11-681	680		3800	


MF11-821	820	±5 ±10 ±20	3800	±5 ±10
MF11-102	1000		3800	
MF11-122	1200		3800	
MF11-152	1500		3800	
MF11-202	2000		4000	
MF11-222	2200		4000	
MF11-272	2700		4000	
MF11-302	3000		4000	
MF11-332	3300		4000	
MF11-392	3900		4000	
MF11-472	4700		4050	
MF11-502	5000		4050	
MF11-562	5600		4050	
MF11-682	6800		4050	
MF11-822	8200		4050	
MF11-103	10000		4050	
MF11-123	12000		4050	
MF11-153	15000		4150	
MF11-203	20000		4300	
MF11-303	30000		4300	
MF11-473	47000		4300	
MF11-503	50000		4300	
MF11-683	68000		4300	
MF11-104	100000		4500	
MF11-124	120000		4700	
MF11-154	150000		4700	
MF11-204	200000		4700	
MF11-304	300000		4700	
MF11-504	500000		4800	
MF11-105	1000000		4900	



尺寸 Dim(mm)	代号 Sym	D _{max}	T _{max}	d ±0.05	F1 ±1	F2 ±1.5	直引线 Straight lead	弯引线 Curved lead	
							L _{min}	L _{1 min}	L _{2 ±2}
型号 Part No									
MF72-□D5		7.0	5	0.6/0.45	5/2.5	3	25	17/5	8/5
MF72-□D7		9.0	5	0.6	5	3	25	17/5	8/5
MF72-□D9		11.0	5.5	0.8/0.6	7.5/5	5/3	25	17/5	8/5
MF72-□D11		13.0	5.5	0.8	7.5/5	5/3	25	17/5	8/5
MF72-□D13		15.5	6	0.8	7.5	5	25	17/5	8/5
MF72-□D15		17.5	6	0.8	10/7.5	5	25	17/5	8/5
MF72-□D20		22.5	7	1.0	10/7.5	/	25	/	/
MF72-□D25		27.5	8	1.0	10	/	25	/	/

Applications

Coverison power-supply, switch power, ups power
 Electronic energy saving lamps,electronic ballast and all kinds of electric heater
 All kinds of RT, display
 Bulb and other lighting lamps




Conventional product electrical performance parameters

Part No.	Mf	25°C Max, Steady State Current(A)	Approx. R of Max. Cur.	Dissi. Coef. (MW/°C)	Thermal time Constant(S)	Operating Temp.(°C)
5D5	5	1	0.353	6	20	
10D5	10	0.7	0.771	6	20	
60D5	60	0.3	1.878	6	18	
200D5	200	0.1	18.70	6	18	
5D7	5	2	0.283	10	30	
8D7	8	1	0.539	9	28	
10D7	10	1	0.616	9	27	
12D7	12	1	0.816	9	27	
16D7	16	0.7	1.003	9	27	
22D7	22	0.6	1.108	9	27	
33D7	33	0.5	1.485	10	28	
200D7	200	0.2	11.65	11	28	
3D9	3	4	0.120	11	35	
4D9	4	3	0.190	11	35	
5D9	5	3	0.210	11	34	
6D9	6	2	0.315	11	34	
8D9	8	2	0.400	11	32	
10D9	10	2	0.458	11	32	
12D9	12	1	0.652	11	32	
16D9	16	1	0.802	11	31	
20D9	20	1	0.864	11	30	
22D9	22	1	0.950	11	30	
30D9	30	1	1.022	11	30	
33D9	33	1	1.124	11	30	
50D9	50	1	1.252	11	30	
60D9	60	0.8	1.502	11	30	
80D9	80	0.8	2.010	11	30	
120D9	120	0.8	3.015	11	30	
200D9	200	0.5	5.007	11	32	
400D9	400	0.2	30.30	11	32	
2.5D11	2.5	5	0.095	13	43	
3D11	3	5	0.100	13	43	
4D11	4	4	0.150	13	44	
5D11	5	4	0.156	13	45	
6D11	6	3	0.240	13	45	

8D11	8	3	0.255	14	47
10D11	10	3	0.275	14	47
12D11	12	2	0.462	14	48
16D11	16	2	0.470	14	50
20D11	20	2	0.512	15	52
22D11	22	2	0.563	15	52
30D11	30	1.5	0.667	15	52
33D11	33	1.5	0.734	15	52
50D11	50	1.5	1.021	15	52
60D11	60	1.5	1.215	15	52
80D11	80	1.2	1.656	15	52
1.3D13	1.3	7	0.062	13	52
1.5D13	1.5	7	0.073	13	60
2.5D13	2.5	6	0.088	13	160
3D13	3	6	0.092	14	60
4D13	4	5	0.120	15	67
5D13	5	5	0.125	15	68
6D13	6	4	0.170	15	65
7D13	7	4	0.188	15	65
8D13	8	4	0.194	15	60
10D13	10	4	0.206	15	65
12D13	12	3	0.316	16	65
15D13	15	3	0.335	16	60
16D13	16	3	0.338	16	60
20D13	20	3	0.372	16	65
30D13	30	2.5	0.517	16	65
47D13	47	2	0.810	17	65
120D13	120	1.2	2.124	16	65
1.3D15	1.3	8	0.048	18	65
1.5D15	1.5	8	0.052	18	68
3D15	3	7	0.075	18	69
5D15	5	6	0.112	18	76
6D15	6	5	0.155	20	76
7D15	7	5	0.173	20	80
8D15	8	5	0.178	20	80
10D15	10	5	0.180	20	80
12D15	12	4	0.250	20	80
15D15	15	4	0.268	21	75
16D15	16	4	0.276	21	75
20D15	20	4	0.288	21	85
30D15	30	3.5	0.438	21	70
47D15	47	3	0.680	21	86
120D15	120	1.8	1.652	22	87
0.7D20	0.7	11	0.018	24	89
1.3D20	1.3	9	0.037	24	88
3D20	3	8	0.055	24	88
5D20	5	7	0.087	24	87
6D20	6	6	0.113	25	103
8D20	8	6	0.142	25	105
10D20	10	6	0.162	25	102
12D20	12	5	0.195	25	100
16D20	16	5	0.212	25	100
0.7D25	0.7	12	0.014	30	120
1.5D25	1.5	10	0.027	30	121
3D25	3	9	0.044	32	124
5D25	5	8	0.070	32	125
8D25	8	7	0.114	33	125
10D25	10	7	0.130	32	125
12D25	12	6	0.156	32	126
16D25	16	6	0.160	35	126

-55~+200

Production Process



Negative temperature coefficient thermistor, also known as NTC thermistor, is a kind of sensor resistance whose resistance value decreases with the increase of temperature. Widely used in various electronic components, such as temperature sensors, resettable fuses and self-adjusting heaters, etc.

PRODUCT CATEGORIES




Home Appliance

[More+](#)



Kitchen

[More+](#)



Home Industry

[More+](#)



New Energy

[More+](#)



Car Industry

[More+](#)



TPE Temperature Sensor

[More+](#)



CERTIFICATES



TUV



CE



TUV



CE



CE



UL



VDE




ROHS

OUR PARTNERS



Our advantage:



Dongguan Linkun Electronic Technology Co., Ltd.



13423305709



huangju@lk-ptc.com



lk-thermistor.com

Room 101, No. 21, Huayuanzai Road, Chongmei, Chashan Town, Dongguan City, Guangdong Province